

■ 諸元表

タイヤサイズ	リムサイズ	パターン LUG	ECO	QUICK	重量 (kg)	外径 (mm)	巾 (mm)	許容荷重 (kg)			
			エコマチック	クイック				0km	6km/h	10km/h	25km/h
3.00-5	2.15B-5	LUG			3.2	267	78	505	435	395	335
3.00-5S	2.15B-5	LUG			2.5	248	72	505	435	395	335
3.50-5	3.00SP-5	LUG			6.2	298	101	605	520	470	400
4.00-8	3.00D-8	MG			10.9	410	103	1,100	950	860	730
4.00-8	3.75-8	RIB			12.5	406	130	1,170	1,010	915	775
5.00-8	3.00D-8	MG	○		16.0	450	122	1,645	1,415	1,285	1,090
15×41/2-8	3.00D-8	MG		○	10.0	376	114	1,210	1,040	940	800
16×6-8	4.33R-8	MG		○	16.2	412	150	1,735	1,495	1,355	1,150
18×7-8	4.33R-8	MG	○	○	20.6	454	157	2,490	2,145	1,945	1,650
5.00-9	3.50D-8	MG			19.1	487	129	1,675	1,445	1,310	1,110
6.00-9	4.00E-9	MG	○		24.5	523	138	2,190	1,885	1,710	1,450
16×5-9	3.50D-8	RIB			12.0	410	125	1,225	1,050	950	810
21×8-9	6.00E-9	MG	○	○	32.5	517	187	3,200	2,755	2,505	2,120
140/55-9	4.00E-9	MG		○	10.1	379	130	1,360	1,170	1,060	900
6.50-10	5.00F-10	MG			33.1	566	162	2,720	2,340	2,125	1,800
23×9-10	6.50F-10	MG		○	46.8	583	204	4,000	3,445	3,125	2,650
200/50-10	6.50F-10	MG		○	23.9	461	191	2,870	2,470	2,240	1,900
7.00-12	5.00S-12	MG	○	○	45.0	652	172	3,380	2,920	2,645	2,240
8.25-12	5.00S-12	MG			63.5	423	187	3,995	3,440	3,120	2,645
23×10-12	8.00G-12	MG		○	49.6	586	234	4,380	3,770	3,420	2,900
27×10-12	8.00G-12	MG			76.1	680	248	4,530	3,900	3,540	3,000
150/100-13	3.75P-13	MG			31.5	621	146	1,995	1,715	1,560	1,320
5.50-15	4.50E-15	HT			38.7	665	154	2,825	2,430	2,205	1,870
6.00-15	4.50E-15	MG			44.7	698	160	3,165	2,725	2,470	2,095
7.00-15	6.00S-15	HT			63.0	729	179	4,115	3,545	3,215	2,725
8.25-15	6.50T-15	MG		○	87.1	813	212	5,510	4,750	4,300	3,650
23×9-15	7.00T-15	MG			59.2	687	218	4,380	3,770	3,125	2,650
250-15	7.00T-15	MG		○	68.0	716	225	5,510	4,745	4,200	3,570
300-15	8.00V-15	MG		○	108.6	815	257	6,795	5,850	5,210	4,410
355/65-15	9.75-15	MG		○	134.7	819	312	9,060	7,000	6,430	5,450
28×12.5-15	9.75-15	MG			88.9	712	295	6,420	5,525	4,575	3,875
7.50-16	6.00GS-16	HT			75.5	794	210	4,605	3,965	3,600	3,050
7.50-20	6.00S-20	HT			86.5	882	200	4,910	3,900	3,520	3,200
8.25-20	7.00T-20	HT			117.0	968	220	5,510	4,400	4,005	3,675
9.00-20	7.00T-20	HT			121.1	974	224	6,795	5,400	4,850	4,450
10.00-20	7.00T-20	MG			166.0	1037	252	7,550	6,000	5,450	5,000
10.00-20	7.50T-20	HT			155.0	1007	248	7,550	6,000	5,450	5,000
12.00-20	8.00T-20	MG			213.0	1090	283	9,515	7,560	6,815	6,250
12.00-24	8.00TG-24	HT			237.0	1178	278	10,115	8,040	7,250	6,650
12.00-24	8.50-24	HT			237.0	1178	278	10,115	8,040	7,250	6,650
14.00-24	10.00WI-24	MG			373.0	1322	333	13,970	11,000	10,000	9,175
16.00-25	11.25-25	MG			589.0	1445	416	18,875	15,000	13,625	12,500